

**LEACHATE TREATMENT BY USING RECIRCULATION
METHOD: A CASE STUDY FROM SEMI AEROBIC SANITARY
LANDFILL SITE**

EZLINA BINTI OTHMAN

**B.Eng (Hons) (Civil)
UNIVERSITI TEKNOLOGI MARA
2006**

**LEACHATE TREATMENT BY USING RECIRCULATION
METHOD: A CASE STUDY FROM SEMI AEROBIC SANITARY
LANDFILL SITE**

By

EZLINA BINTI OTHMAN

Report is submitted as the requirement for the degree of
Bachelor Engineering (Hons) (Civil)

**UNIVERSITI TEKNOLOGI MARA
NOVEMBER 2006**

DECLARATION BY THE CANDIDATE

I, Ezlina binti Othman (2003359011) confirm that work is my own and that appropriate credit has been given where reference has been made to the work of others.

_____ 1st December, 2006

ACKNOWLEDGEMENT

Primarily, thank you God because enable this report Final Year Project II (KJC 537) to be completed. With a special gratitude for my guardians because of their supported and always give me an advice in my studies.

I would like to express a grateful appreciation to my supervisor, Mr. Mohamed Ali bin. Abd. Karim, because of his support and guidance for me during I'm doing this report. Without his guidance, I might not be able to finish this report in a proper way.

I wish to acknowledge Mr. Sufian (Site Manager) and Mr. Mohd Fadzli B. Darus (Site Engineer) and Mr. Harun B. Puniran (Environmental Officer) for Idaman Bersih Sdn. Bhd. for all their willingness and kindness giving an explanation and some information about Pulau Burung Sanitary Landfill.

Special gratitude to Mrs. Rokibah and Mrs. Suzana as Laboratory Technician for their help during I'm doing my laboratory work.

Lastly, I also want to thank all others who have, in one way or other, given me invaluable help, assistance and advice.

ABSTRACT

Municipal Solid Waste (MSW) is considered as a nuisance or is said to have a negative value, which suggests that they are cheaper to throw away than to recover. A laboratory scale used leachate recirculation method is done for 3 months to observe the capability of the waste to treat the leachate. The leachate sample quality was taking by using eight parameter that were pH, COD, DO, SS, VSS, nitrate, turbidity and temperature. After 3 months doing the recirculation, the pH value is still in the range of alkali, while COD shows an increasing value within 24th day's operation by optimum value of 10840 mg/L. However, the quality of leachate is improved in COD because the optimum value then decreases to 2485 mg/L on 64th day's operation. Another parameter such as turbidity, SS and VSS of the leachate are also reaching their optimum value within 24th day's operation with 385.7 NTU, 700 mg/L and 600 mg/L. However these parameter start to improved after 27th day's operation by showing the decreasing value of 131.7 NTU, 240 mg/L and 140 mg/L on 64th day's operation. From overall, the leachate recirculation method is capable to treat the leachate consequently reduced the contaminants within the leachate. It is suggested that more research about leachate recirculation method will be done in future.

Keywords – Municipal Solid Waste, leachate recirculation method, treat, contaminants.